

CrossWind

MEDIUM RADIAL TRUCK TIRES

2016



CrossWind



MISSION

CROSSWIND is dedicated to providing the highest quality and value to our customers. Each tire is built to perform, using advanced technology and innovation.

CROSSWIND brings you an ever-increasing selection of commercial truck tires – from Steer, All-Position and Trailer to Mixed Service tread designs. Whether you are looking for a Long Haul, Regional, Mixed Service or On/Off-Road application, CROSSWIND has you covered. Plus, every tire is backed by a comprehensive warranty.

CROSSWIND brings you quality and value with every tire.



SIZE CHART

SIZE	LONG HAUL				REGIONAL / METRO										MIXED SERVICE		ON / OFF-ROAD	
	LHS	CSD	TRL	TRL	AP	AP	AP	AP	AP	AP	OSD	OSD	OSD	OSD	AP MS	WIDE MS	TRAC	TRAC
	CWS201sw	CWD210sw	CWT209sw	CWT226sw	CWA202sw	CWA207sw	CWA208	CWA203	CWA205	CWA206	CWD211	CWD213	CWD212	CWD215	CWA217	CWA218	CWD216	CWD219
215/75R17.5									H									
235/75R17.5										H								
225/70R19.5								G						G				
245/70R19.5								H						G				
265/70R19.5								H									H	
9.00R20															H			
10.00R20															J			
11.00R20															J			
12.00R20															J			
11R22.5	H	H	G	G	H						H				H			H
12R22.5							J					J						
13R22.5													J					
295/80R22.5						J					G							
315/80R22.5						J						J			L			
295/75R22.5	G	G	G	G	G													
255/70R22.5								H										
275/70R22.5								H										
385/65R22.5																L		
425/65R22.5																L		
11R24.5	H	H	G	G	H						H				H			H
285/75R24.5	G	G	G	G	G						G							

SW = SMARTWAY VERIFIED

TABLE OF CONTENTS

LONG HAUL

CWS201sw	LINE HAUL STEER.....	1
CWD210sw	CLOSED SHOULDER DRIVE.....	1
CWT209sw	FREE ROLLING TRAILER	1
CWT226sw	DECOUPLING GROOVE FREE ROLLING TRAILER.....	2

REGIONAL

CWA202sw	STEER / ALL-POSITION.....	2
CWA207sw	STEER / ALL-POSITION.....	2
CWA208	REGIONAL ALL-POSITION	3
CWA203	REGIONAL / METRO ALL-POSITION	3
CWA205	REGIONAL / METRO ALL-POSITION	3
CWA206	REGIONAL / METRO ALL-POSITION	4
CWD211	OPEN SHOULDER DRIVE.....	4
CWD213	OPEN SHOULDER DRIVE.....	4
CWD212	OPEN SHOULDER DRIVE.....	5
CWD215	METRO DRIVE	5

MIXED SERVICE

CWA217	MIXED SERVICE ALL-POSITION	5
CWA218	MIXED SERVICE WIDE BASE.....	6

ON/OFF-ROAD

CWD216	ON / OFF-ROAD TRACTION.....	6
CWD219	ON / OFF-ROAD TRACTION.....	6

CWS20_{sw} LINE HAUL STEER**FEATURES & BENEFITS**

- 5-rib tread design with special tread compounds enhances even wear and traction in line-haul steer axle positions.
- Multiple sipes and shoulder decoupling grooves enhance tire wear and traction.
- Bead and belt designed package for increased tire performance and multiple retreads.
- SmartWay approved, low rolling resistance tire.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005703	11R22.5	H/16	TL	8.25	18	41.5	11.0	6610/6005	120/120	M	146/143	120
211005704	295/75R22.5	G/14	TL	9.00	18	39.9	11.7	6175/5675	110/110	M	144/141	111
211005705	11R24.5	H/16	TL	8.25	18	43.5	11.0	7160/6610	120/120	M	149/146	132
211005706	285/75R24.5	G/14	TL	8.25	18	41.3	11.1	6175/5675	110/110	M	144/141	119

CWD210_{sw} CLOSED SHOULDER DRIVE**FEATURES & BENEFITS**

- Deep 28/32nds long haul highway closed shoulder drive tire for long mileage and even tread wear.
- Advanced tread compound for low rolling resistance and increased fuel economy.
- Tapered groove technology to minimize stone retention and increase casing life.
- SmartWay approved, low rolling resistance tire.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005729	11R22.5	H/16	TL	8.25	28	41.9	11.0	6610/6005	120/120	M	146/143	122
211005730	295/75R22.5	G/14	TL	9.00	28	40.2	11.7	6175/5675	110/110	M	144/141	118
211005731	11R24.5	H/16	TL	8.25	28	43.9	11.0	7160/6610	120/120	M	149/146	140
211005732	285/75R24.5	G/14	TL	8.25	28	41.6	11.1	6175/5675	110/110	M	144/141	128

CWT209_{sw} FREE ROLLING TRAILER**FEATURES & BENEFITS**

- 5-rib tread design delivers premium handling, stability and traction.
- Solid shoulder for even wear in higher scrub applications.
- Enhanced siping provides traction and fights irregular wear.
- SmartWay approved, low rolling resistance tire.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005725	11R22.5	G/14	TL	8.25	13	41.5	11.0	6175/5840	105/105	M	144/142	102
211005726	295/75R22.5	G/14	TL	9.00	13	39.9	11.7	6175/5675	110/110	M	144/141	100
211005727	11R24.5	G/14	TL	8.25	14	43.5	11.0	6610/6005	105/105	M	146/143	117
211005728	285/75R24.5	G/14	TL	8.25	14	41.3	11.1	6175/5675	110/110	M	144/141	108

CWT226sw

DECOUPLING GROOVE FREE ROLLING TRAILER

**FEATURES & BENEFITS**

- Decoupling groove helps to resist irregular wear.
- 5-rib design provides excellent straight running performance.
- Four circumferential grooves aid water evacuation for enhanced traction.
- SmartWay approved, low rolling resistance tire.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005721	11R22.5	G/14	TL	8.25	12	41.5	11.0	6175/5840	105/105	M	144/142	107
211005722	295/75R22.5	G/14	TL	9.00	13	39.9	11.7	6175/5675	110/110	M	144/141	103
211005723	11R24.5	G/14	TL	8.25	12	43.5	11.0	6610/6005	105/105	M	146/143	119
211005724	285/75R24.5	G/14	TL	8.25	12	41.3	11.1	6175/5675	110/110	M	144/141	107

CWA202sw

STEER / ALL-POSITION

**FEATURES & BENEFITS**

- 5-rib tread pattern with wide shoulders for even load distribution.
- Enhanced siping and wide grooves deliver premium wet and dry traction.
- Stone ejectors protect and minimize the penetration of rocks into the casing.
- SmartWay approved, low rolling resistance tire.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005707	11R22.5	H/16	TL	8.25	18	41.5	11.0	6610/6005	120/120	M	146/143	120
211005708	295/75R22.5	G/14	TL	9.00	18	39.9	11.7	6175/5675	110/110	M	144/141	109
211005709	11R24.5	H/16	TL	8.25	18	43.5	11.0	7160/6610	120/120	M	149/146	132
211005710	285/75R24.5	G/14	TL	8.25	18	41.3	11.1	6175/5675	110/110	M	144/141	118

CWA207sw

STEER / ALL-POSITION

**FEATURES & BENEFITS**

- 5-rib tread pattern with wide shoulders promotes durability and even wear.
- Wide grooves designed for hydroplaning resistance.
- Enhanced siping provides stability and safety when running on wet and slippery roads.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005719	315/80R22.5	J/18	TL	9.00	18	42.4	12.3	8270/7610	120/120	M	154/151	137
211005718	295/80R22.5*	J/18	TL	9.00	18	41.1	11.7	7830/7160	130/130	M	152/149	126

* Denotes non SmartWay

CWA208

REGIONAL ALL-POSITION

FEATURES & BENEFITS

- Wide shoulders provide even load distribution.
- Tread design helps resist stone retention.
- 4-rib tread pattern provides strong wear resistance and low heat generation.
- Chip and abrasion resistant tread compounds offer long mileage and wear.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005720	12R22.5	J/18	TL	9.00	23	42.7	11.8	7825/7160	135/135	K	152/149	155

CWA203

REGIONAL / METRO ALL-POSITION

FEATURES & BENEFITS

- 5-rib tread pattern and wide shoulders for even load distribution.
- Solid shoulder fights irregular wear in high scrub applications.
- Special groove shape design for improved rib tear resistance.
- Wide grooves designed for hydroplaning resistance.
- Cross-rib siping fights wear and improves wet traction.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005713	225/70R19.5	G/14	TL	6.75	16	31.9	8.9	3970/3750	110/110	M	128/126	64
211005714	245/70R19.5	H/16	TL	7.50	16	33.0	9.8	4805/4540	120/120	M	135/133	77
211005715	265/70R19.5	H/16	TL	7.50	17	34.1	10.3	5510/5205	112/112	M	140/138	88
211005711	255/70R22.5	H/16	TL	7.50	18	36.6	10.0	5510/5070	120/120	M	140/137	93
211005712	275/70R22.5	H/16	TL	8.25	18	37.7	10.9	6945/6395	130/130	M	148/145	103

CWA205

REGIONAL / METRO ALL-POSITION

FEATURES & BENEFITS

- 5-rib tread pattern and wide shoulders for even load distribution.
- Special groove shape design for improved rib tear resistance.
- Sipes improve traction in wet conditions and dissipate heat for prolonged tread life.
- Wide grooves designed for hydroplaning resistance.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005716	215/75R17.5	H/16	TL	6.00	16	30.2	8.35	4805/4540	123/123	L	135/133	60

CWA206

REGIONAL / METRO ALL-POSITION



FEATURES & BENEFITS

- 4 wide grooves to channel water out of footprint for wet traction.
- Solid shoulder fights irregular wear in high scrub applications.
- 5-rib tread pattern and wide shoulders for even load distribution.
- Sipes improve traction in wet conditions and dissipate heat for prolonged tread life.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005717	235/75R17.5	H/16	TL	6.75	16	31.4	9.2	5675/5510	123/123	L	141/140	66

CWD211

OPEN SHOULDER DRIVE



FEATURES & BENEFITS

- Block siping for increased traction and performance in varying road conditions.
- Open shoulder lugs for traction and center ribs for increased stability and long wear.
- Deep original tread depth delivers maximum tread life.
- Tread pattern provides excellent drainage and slip resistance.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005733	11R22.5	H/16	TL	8.25	26	41.5	11.0	6610/6005	120/120	L	146/143	128
211005734	295/75R22.5	G/14	TL	9.00	26	39.9	11.7	6175/5675	110/110	M	144/141	118
211005735	11R24.5	H/16	TL	8.25	26	43.5	11.0	7160/6610	120/120	L	149/146	141
211005736	285/75R24.5	G/14	TL	8.25	26	41.3	11.1	6175/5675	110/110	M	144/141	129

CWD213

OPEN SHOULDER DRIVE



FEATURES & BENEFITS

- Open shoulder design enhances traction in multiple applications.
- Integrated central rib design for improved stability.
- Interlocking lugs for smooth even wear.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	INFLATION PRESSURE (PSI)	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005738	12R22.5	J/18	TL	9.00	27	42.4	11.8	7825/7160	135/135	L	152/149	164
211002351	315/80R22.5*	J/18	TL	9.00	27	42.4	12.3	8270/7610	120/120	L	154/151	198

* Branded Linglong LDL813

CWD212

OPEN SHOULDER DRIVE

FEATURES & BENEFITS

- Excellent traction and endurance performance.
- Chip, cut and abrasion resistant tread compounds offer long mileage and wear.
- Deep tread depth increases mileage and service life.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005784	13R22.5	J/18	TL	9.75	27	44.6	12.4	8820/7385	127/127	K	156/150	172

CWD215

METRO DRIVE

FEATURES & BENEFITS

- Deep and rigid block design for good traction and excellent road manners.
- Chip and abrasion resistant tread compounds offer long mileage and wear.
- Lug siping to maximize traction in all weather conditions.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005739	225/70R19.5	G/14	TL	6.75	18	31.9	8.9	3970/3750	110/110	M	128/126	66
211005740	245/70R19.5	G/14	TL	7.50	20	33.0	9.8	4540/4300	110/110	M	133/131	79

CWA217

MIXED SERVICE ALL-POSITION

FEATURES & BENEFITS

- Chip, cut and abrasion resistant tread compounds offer long mileage and wear.
- Zigzag grooves help to resist stone retention.
- Rugged 4-rib design for outstanding off road and wet traction.
- Shoulder lug grooves designed for excellent traction.



ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211002777	9.00R20*	H/16	TT	7.00	18	40.1	10.2	6175/5840	130/130	K	144/142	124
211000166	10.00R20*	J/18	TT	7.50	19	41.5	10.9	7160/6610	135/135	K	149/146	134
211000454	11.00R20*	J/18	TT	8.00	20	42.7	11.5	7830/7160	135/135	K	152/149	156
211001097	12.00R20*	J/18	TT	8.00	21	44.3	12.4	8270/7610	120/120	K	154/151	166
211005742	11R22.5	H/16	TL	8.25	20	41.5	11.0	6610/6005	120/120	K	146/143	121
211005744	315/80R22.5	L/20	TL	9.00	22	42.4	12.3	9090/8270	130/130	K	157/154	146
211005743	11R24.5	H/16	TL	8.25	20	43.5	11.0	7160/6610	120/120	K	149/146	136

* Branded Linglong LLA08

CWA218

MIXED SERVICE WIDE BASE

**FEATURES & BENEFITS**

- Chip, cut and abrasion resistant tread compounds offer long mileage and wear.
- Heavy-duty belt package increases durability, uniform wear and stability.
- Strong wear resistance compounds and wide footprint.
- Continuous shoulder design for improved stability.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005745	385/65R22.5	L/20	TL	11.75	21	42	15	9920/N/A	130/N/A	K	160/N/A	170
211002572	425/65R22.5*	L/20	TL	13.00	23	44	17	11355/N/A	120/N/A	J	165/N/A	198

* Branded Linglong LLA38

CWD216

ON / OFF-ROAD TRACTION

**FEATURES & BENEFITS**

- Integrated center tie bar reduces irregular wear and increases stability.
- Optimized on the drive axle for on or light duty off road conditions.
- Deep and rigid block design for long life and good traction.
- Chip, cut and abrasion resistant tread compounds offer long mileage and wear.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005741	265/70R19.5	H/16	TL	7.50	20	34.1	10.3	5510/5205	112/112	M	140/138	92

CWD219

ON / OFF-ROAD TRACTION

**FEATURES & BENEFITS**

- Optimized on the drive axle for on/off road conditions.
- Deep and rigid block design for excellent traction.
- Chip, cut and abrasion resistant tread compounds offer long mileage and wear.
- Stone ejectors protect and minimize the penetration of rocks into the casing.

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
211005746	11R22.5	H/16	TL	8.25	29	41.9	11.0	6610/6005	120/120	K	146/143	130
211005747	11R24.5	H/16	TL	8.25	32	43.9	11.0	7160/6610	120/120	G	149/146	147

CrossWind

tbcbrands.com • treadxpress.com • 1-866-822-4968

Distributed and Marketed by

TBCBrands

4300 TBC Way, Palm Beach Gardens, FL 33410