SIERRA TIRES

2018

SIZE CHART

	STEER/ALL-POSITION/TRAILER				DRIVE				MIXED SERVICE	WIDE BASE
	STR	STR/AP	AP	TRL	CSD	OSD	OSD	WINTER	AP	AP
SIZE	SR256	SR803	SR562	SR809	SR369	SR366	SR316	SR318	SR518	SR216
215/75R17.5			H							
235/75R17.5			H							
225/70R19.5			G				G			
245/70R19.5			G				H			
265/70R19.5			G				H			
285/70R19.5			H							
10.00R20									J	
11.00R20									J	
11R22.5	G/H	G/H		G	G/H	H		H	H	
11R24.5	G/H	G/H			G/H	H			H	
295/75R22.5	G	G		G	G					
285/75R24.5	G	G			G					
255/70R22.5		H								
275/70R22.5		H								
295/80R22.5		J								
315/80R22.5		L							L	
12R22.5									H	
385/65R22.5										L
425/65R22.5										L

TABLE OF CONTENTS

STEER/ALL-POSITION/TRAILER

SR256 1

SR803 1

SR562 2

SR809 2

DRIVE

SR369 3

SR366 3

SR316 4

SR318 4

MIXED SERVICE

SR518 5

WIDE BASE

SR216 5

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.

SR256 STEER

FEATURES & BENEFITS

- DECOUPLING GROOVE TO MINIMIZE IRRGULAR WEAR
- FIVE-RIB DESIGN PROMOTES EVEN WEAR AND LONG TIRE LIFE
- ENHANCED SIPING FOR WATER DISPERSION
- STONE EJECTORS TO MINIMIZE STONE RETENTION

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
9720114	11R22.5	G/14	144/142M	TL	8.25	19	41.5	11.0	6175/5840	105/105	116.07
97201	11R22.5	H/16	146/143M	TL	8.25	19	41.5	10.9	6610/6005	120/120	120.15
9720714	11R24.5	G/14	146/143M	TL	8.25	19	43.5	11.0	6610/6005	105/105	126.04
97207	11R24.5	H/16	149/146M	TL	8.25	19	43.5	10.9	7160/6610	120/120	131.39
9720214	295/75R22.5	G/14	144/141M	TL	9.00	19	39.9	11.7	6175/5675	110/110	110.67
9720414	285/75R24.5	G/14	144/141M	TL	8.25	19	41.3	11.1	6175/5675	110/110	115.17

SR803 ALL-POSITION

FEATURES & BENEFITS

- EXCELLENT STABILITY AND RESISTANCE TO IRREGULAR WEAR
- STONE EJECTORS PROVIDE GOOD SELF CLEANING
- FOUR-GROOVE DESIGN FOR ENHANCED WATER DISPERSION
- RIB SIPING FOR INCREASED TRACTION
- DEEP ORIGINAL TREAD DEPTH PROMOTES LONG TIRE LIFE

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
9730114	11R22.5	G/14	144/142M	TL	8.25	20	41.5	11.0	6175/5840	105/105	116.27
97301	11R22.5	H/16	146/143M	TL	8.25	19	41.5	10.9	6610/6005	120/120	125.22
9730314	11R24.5	G/14	146/143M	TL	8.25	19	43.5	11.0	6610/6005	105/105	126.04
97303	11R24.5	H/16	149/146L	TL	8.25	19	43.5	10.9	7160/6610	120/120	132.76
9731214	295/75R22.5	G/14	144/141M	TL	9.00	19	39.9	11.7	6175/5675	110/110	110.67
9730414	285/75R24.5	G/14	144/141M	TL	8.25	19	41.3	11.1	6175/5675	110/110	115.16
97308	255/70R22.5	H/16	140/137M	TL	7.50	16	36.6	10.0	5520/5070	120/120	97.00
97320	275/70R22.5	H/16	148/145M	TL	8.25	18	37.7	10.9	6940/6385	130/130	111.33
97313	295/80R22.5	J/18	152/149M	TL	9.00	19	41.1	11.7	7830/7160	125/125	130.95
97310	315/80R22.5	L/20	157/154M	TL	9.00	19	42.4	12.3	9090/8270	130/130	141.09

SR562 ALL-POSITION/TRAILER

FEATURES & BENEFITS

- RIB TIRE WITH FOUR CIRCUMFERENTIAL GROOVES
- SHOULDER NOTCHING AND SIPES EFFECTIVELY DISPERSE SHOULDER HEAT TO IMPROVE ENDURANCE
- CONVEX PLATFORM ON THE BOTTOM OF THE GROOVE PREVENTS GROOVE STRAIN AND CRACKING

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
TRAILER APPLICATION											
97008	215/75R17.5	H/16	135/133J	TL	6.00	16	30.2	8.3	4805/4540	123/123	58.86
97001	235/75R17.5	H/16	143/141M	TL	6.75	16	31.4	9.2	6005/5675	120/120	70.55
ALL-POSITION											
97002	225/70R19.5	G/14	128/126L	TL	6.75	18	31.9	8.9	3970/3750	110/110	70.33
97003	245/70R19.5	G/14	133/131L	TL	7.50	18	33.0	9.8	4540/4300	110/110	74.96
97004	265/70R19.5	G/14	140/138L	TL	7.50	18	34.1	10.4	5070/4675	110/110	83.11
97015	285/70R19.5	H/16	146/144L	TL	8.25	18	35.2	11.1	6610/6175	130/130	86.28

SR809 TRAILER

FEATURES & BENEFITS

- SHALLOW DEPTH TRAILER TIRE
- EXCELLENT STABILITY AND REISISTANCE TO IRREGULAR WEAR
- FOUR-GROOVE DESIGN FOR ENHANCED WATER DISPERSION
- RIB SIPING FOR INCREASED TRACTION

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
9736914	11R22.5	G/14	144/142M	TL	8.25	13	41.5	11.0	6175/5840	105/105	127.00
9731414	295/75R22.5	G/14	144/141M	TL	9.00	13	39.9	11.7	6175/5675	110/110	112.00

SR369 CLOSED-SHOULDER DRIVE

FEATURES & BENEFITS

- DEEP LONG LASTING TREAD
- SPECIAL GROOVE DESIGN PREVENTS STONE RETENTION TO PROTECT THE CASING
- SOLID CLOSED-SHOULDER PROMOTES EVEN WEAR
- WIDE TREAD DESIGN WITH SIPING IN TREAD BLOCKS FOR INCREASED TRACTION

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
9710114	11R22.5	G/14	144/142L	TL	8.25	29	41.9	11.0	6175/5840	105/105	127.34
97101	11R22.5	H/16	146/143L	TL	8.25	29	41.9	10.9	6610/6005	120/120	129.41
9710314	11R24.5	G/14	146/143L	TL	8.25	29	43.9	11.0	6610/6005	105/105	138.03
97103	11R24.5	H/16	149/146L	TL	8.25	29	43.9	10.9	7160/6610	120/120	141.54
9710214	295/75R22.5	G/14	144/141L	TL	9.00	29	40.2	11.7	6175/5675	110/110	122.80
9710414	285/75R24.5	G/14	144/141L	TL	8.25	29	41.6	11.1	6175/5675	110/110	124.80

SR366 OPEN-SHOULDER DRIVE

FEATURES & BENEFITS

- DEEP TREAD DEPTH FOR EXCELLENT TRACTION
- OPEN-SHOULDER DESIGN PROVIDES HEAT DISSIPATION TO ASSIST WITH TIRE DURABILITY
- SPECIAL TREAD COMPOUNDS TO RESIST CUTTING AND CHIPPING
- SIPING IN TREAD BLOCKS FOR ENHANCED TRACTION

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
97602	11R22.5	H/16	146/143M	TL	8.25	29	41.9	10.9	6610/6005	120/120	131.61
97604	11R24.5	H/16	149/146M	TL	8.25	29	43.9	10.9	7160/6610	120/120	144.62

SR316 DRIVE

FEATURES & BENEFITS

- REINFORCED RIBS ON THE GROOVE BOTTOM
- WIDE TREAD DESIGN FOR IMPROVED WEAR
- DEEP ORIGINAL TREAD DEPTH

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
978005	225/70R19.5	G/14	128/126M	TL	6.75	19	31.9	8.9	3970/3750	110/110	72.31
978006	245/70R19.5	H/16	136/134L	TL	7.50	19	33.0	9.8	4940/4665	120/120	76.28
978007	265/70R19.5	H/16	140/138M	TL	7.50	20	34.1	10.3	5500/5205	110/110	85.54

SR318 WINTER DRIVE

FEATURES & BENEFITS

- OPEN-SHOULDER DESIGN PROMOTES SELF CLEANING
- CORRUGATED SIPING FOR INCREASED TRACTION
- BLOCK PATTERN PROVIDES BETTER HANDLING IN MUD AND SNOW

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
979003	11R22.5	H/16	146/143M	TL	8.25	26	41.5	10.9	6614/6008	120/120	123.22

SR518 MIXED SERVICE

FEATURES & BENEFITS

- FOUR-RIB ZIGZAG TIRE DESIGN SUITABLE FOR MIXED SERVICE APPLICATIONS
- SHOULDER DESIGN FOR INCREASED TRACTION
- SPECIAL TREAD COMPOUNDS TO RESIST CHIPPING AND CHUNKING

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
97401	10.00R20	J/18	149/146K	TT	7.50	19	41.5	10.9	7160/6610	135/135	122.88
97402*	11.00R20	J/18	152/149K	TT	8.00	20	42.7	11.5	7830/7160	135/135	142.04
97405	11R22.5	H/16	146/143L	TL	8.25	20	41.5	10.9	6610/6005	120/120	123.50
97409	11R24.5	H/16	149/146L	TL	8.25	20	43.5	10.9	7160/6610	120/120	133.93
97410	12R22.5	H/16	152/149K	TL	9.00	21	42.7	11.8	7830/7160	135/135	135.74
97408	315/80R22.5	L/20	157/154K	TL	9.00	21	42.7	11.8	9090/8270	130/130	139.55

*Brand may vary

SR216 WIDE BASE ON/OFF-HIGHWAY

FEATURES & BENEFITS

- MULTI-PURPOSE TREAD DESIGN FOR ON/OFF-HIGHWAY APPLICATIONS
- FIVE CIRCUMFERENTIAL GROOVES FOR CONTROL PERFORMANCE
- VARIABLE PITCH DESIGN EFFECTIVELY REDUCES DRIVING NOISE
- WIDE OUTER SHOULDERS FOR INCREASED STABILITY

PRODUCT CODE	TIRE SIZE	LR/PR	SERVICE DESCRIPTION	TYPE	RIM (Inch)	TREAD DEPTH (32/Inch)	OVERALL DIAMETER (Inch)	SECTION WIDTH (Inch)	MAX LOAD SINGLE/DUAL (lbs)	PSI SINGLE/DUAL	WEIGHT (lbs)
97703	385/65R22.5	L/20	160/L	TL	11.75	20	42.2	15.3	9930/	130/	164.46
97705	425/65R22.5	L/20	164/K	TL	12.25	20	44.3	16.6	11000/	120/	193.12

NOTES

NOTES

tbcbrands.com • treadxpress.com • 1-866-822-4968

ST-USCA-TC – 0518

Distributed and Marketed by
TBCBrands
4300 TBC Way, Palm Beach Gardens, FL 33410