

Trail Traxx

All-Terrain

CrossWind

**ALL
NEW**

**Everyday
commute
on the road**

3PMS Certified



Optimized Block Pattern

- Enhances on and off-road traction
- Allows excellent handling stability
- Provides longer tread life

High Density Sipes

- Provides superior snow and wet performance

Sidewall

- Reinforced sidewalls to reduce punctures and damages from rocks and sharp objects

Anti-Stones Design

- Ejects stone from grooves
- Adds grip to deep mud, snow or slush

**A rigorous
adventure
off road**

The all-new Trail Traxx all-terrain tire is a good choice for drivers who want a versatile tire for an everyday commute, as well as planning an adventure for those off-road capabilities. The new tread design offers a balance of traction, durability and comfort allowing you to drive confidently in unpredictable weather conditions such as rain, ice, or snow.

Sizes Available

34

Rim Sizes

16" - 22"

Speed Ratings

H, S, T, Q

Popular sizes and fitments that are compatible with Ford F150/F250/F350, Ford Explorer, Chevy Silverado, Dodge Durango, Ford Expedition, Chevy Tahoe and more.



Free replacement
first 2/32" of treadwear
for workmanship
and material

www.tbcbrands.com/tire-brands/crosswind

Scan here with your mobile device to
view more of CrossWind products



CrossWind

Trail Traxx

All-Terrain

	ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	STANDARD RIM	SECTION WIDTH (IN.)	OVERALL DIAM.	SINGLE MAX. LOAD LBS@PSI	DUAL MAX. LOAD LBS@PSI	SHIP WEIGHT (LBS.)
16	CROS-CTL53	235/70R16	106S		580AB	12.0	BLK	7.00	9.5	29.00	2094@36		32.95
	CROS-CTL79	245/75R16	111S		580AB	13.4	BLK	7.00	9.8	30.50	2403@36		34.98
	CROS-CTL81	265/75R16	116S		580AB	13.4	BLK	7.50	10.5	31.65	2756@36		39.80
	CROS-CTL93	265/70R16	112S		580AB	13.4	BLK	8.00	10.7	30.65	2469@36		38.91
	CROS-CTL26	LT225/75R16	115/112Q	E		14.2	BLK	6.00	8.8	29.29	2680@80	2470@80	38.30
	CROS-CTL38	LT245/75R16	120/116Q	E		15.4	BLK	7.00	9.8	30.47	3042@80	2778@80	44.02
	CROS-CTL39	LT265/75R16	123/120Q	E		15.4	BLK	7.50	10.5	31.65	3415@80	3085@80	48.95
	CROS-CTL68	LT285/75R16	126/123Q	E		16.4	BLK	8.00	11.3	32.83	3750@80	3415@80	54.82
	CROS-CTL67	245/65R17	111H	XL	580AB	13.4	BLK	7.00	9.8	29.55	2403@42		34.53
17	CROS-CTL87	265/70R17	115S		580AB	13.4	BLK	8.00	10.7	31.68	2679@36		41.36
	CROS-CTL58	265/65R17	116S	XL	580AB	13.4	BLK	8.00	10.7	30.57	2756@42		37.84
	CROS-CTL82	285/70R17	116T		580AB	13.4	BLK	8.50	11.5	32.78	2756@36		43.42
	CROS-CTL19	LT245/75R17	121/118Q	E		15.4	BLK	7.00	9.8	31.50	3195@80	2910@80	45.42
	CROS-CTL92	LT265/70R17	123/120Q	E		15.4	BLK	8.00	10.7	31.65	3415@80	3085@80	49.64
	CROS-CTL84	LT285/70R17	126/123Q	E		16.4	BLK	8.50	11.5	32.76	3750@80	3415@80	54.89
	CROS-CTL02	LT315/70R17	126/123Q	E		16.4	BLK	9.50	12.7	34.41	3750@65	3415@65	67.91
	CROS-CTL94	35x12.50R17LT	125Q	E		15.7	BLK	10.00	12.5	34.52	3640@65		67.91
18	CROS-CTL52	255/70R18	113T		580AB	13.4	BLK	7.50	10.2	32.11	2535@36		40.14
	CROS-CTL22	265/70R18	116T		580AB	13.4	BLK	8.00	10.7	32.66	2756@36		41.85
	CROS-CTL91	265/60R18	110T		580AB	11.3	BLK	8.00	10.7	30.54	2336@36		38.97
	CROS-CTL63	275/65R18	116T		580AB	13.4	BLK	8.00	11.0	32.11	2756@36		41.45
	CROS-CTL72	LT275/70R18	125/122Q	E		15.4	BLK	8.00	11.0	33.19	3640@80	3305@80	52.99
	CROS-CTL40	LT275/65R18	123/120Q	E		15.4	BLK	8.00	11.0	32.09	3415@80	3085@80	49.88
	CROS-CTL23	LT295/70R18	129/126Q	E		16.4	BLK	8.50	11.8	34.29	4080@80	3750@80	63.24
	CROS-CTL95	35x12.50R18LT	128Q	F		15.7	BLK	10.00	12.5	34.52	3970@80		67.69
20	CROS-CTL15	275/60R20	115T		580AB	11.3	BLK	8.00	11.0	33.02	2679@36		42.53
	CROS-CTL48	275/55R20	117S	XL	580AB	11.3	BLK	8.50	11.2	31.91	2833@42		38.38
	CROS-CTL43	LT275/65R20	126/123Q	E		15.4	BLK	8.00	11.0	34.09	3750@80	3415@80	54.33
	CROS-CTL80	LT285/60R20	125/122Q	E		16.4	BLK	8.50	11.5	33.46	3640@80	3305@80	60.34
	CROS-CTL78	LT285/55R20	122/119Q	E		16.4	BLK	9.00	11.7	32.36	3305@80	3000@80	53.34
	CROS-CTL88	33x12.50R20LT	119Q	F		15.7	BLK	10.00	12.5	32.52	3000@80		63.68
	CROS-CTL71	35x12.50R20LT	125Q	F		15.7	BLK	10.00	12.5	34.52	3640@80		64.18
22	CROS-CTL31	285/45R22	110Q		580AB	11.3	BLK	9.50	11.2	32.11	2337@36		42.97
	CROS-CTL90	35X12.50R22LT	121Q	F		15.7	BLK	10.00	12.5	34.52	3195@80		68.14